





LEFT SIDE VIEW



RIGHT SIDE VIEW

BACK VIEW

MUNCHKIN BOILER DIMENSIONS AND SPECIFICATIONS

MODEL NUMBER	BTU/HR INPUT LOW FIRE	BTU/HR INPUT HIGH FIRE	A	B	C	D	E	F	G	H	J	K	L	M	N	O	P	VENT SIZE	AIR INLET	GAS CONN.	SUP. RET.	I.B.R.	SHIPPING WEIGHT
80M	27,000	80,000	20.12"	13.00"	25.88"	21.50"	14.87"	16.25"	4.00"	7.00"	18.75"	9.00"	18.25"	9.13"	5.00"	4.66"	8.44"	3"	3"	3/4"	1-1/4"	64,000	75 lbs.
140M	46,000	140,000	20.12"	13.00"	25.88"	21.81"	14.87"	24.50"	4.00"	14.75"	18.75"	9.00"	18.25"	9.13"	5.00"	7.67"	16.47"	3"	3"	3/4"	1-1/4"	112,000	101 lbs.
199M	66,000	199,000	20.12"	13.00"	25.88"	21.81"	14.87"	24.50"	4.00"	14.75"	18.75"	9.00"	18.25"	9.13"	5.00"	7.67"	16.47"	3"	3"	3/4"	1-1/4"	159,000	111 lbs.

MUNCHKIN BOILER AMP DRAW DATA

MODEL NUMBER	CIRCULATOR	CONTROL	APPROX. TOTAL AMPS
80/140/199M	4.0	2.3	6.3
80/140/199MHA	3.0	3.3	6.3